

KENTALROOF-A 120



ROOF FAN WITH FOLDING SYSTEM AND ALUMINIUM COWL 120°C

MANUFACTURING FEATURES:

- Protection cowl made of anticorrosive treated aluminum easily removable for motor and impeller maintenance thanks to the integrated folding system.
- The design of the cowl with a **rounded shape** is specific to minimize the risk of water ingress due to rain (including rain).
- Equipped with a **hinged system** to open the motor-impeller set. This system allows easy maintenance and cleaning of the set without the need to disassemble the entire structure. The opening is possible in 2 inclinations: approximately 45° and 90°, as required by the intervention.
- Structure in anticorrosive galvanized steel and support frame for adaptation to the roof with anti-bird protection grid.
- High-performance, backward-curved blade (reaction) impellers designed to work without scroll. Self-cleaning system, built in galvanized steel treated with anti-corrosion.
- Standard asynchronous squirrel cage motor with IP-55 protection and Class F insulation. Standard voltages 230V 50Hz for single phase motors, 230/400V 50Hz for three phase motors up to 4kW & 400/690V 50Hz for higher powers and 400V 50Hz for 2 speed motors.


Accessories



AC



BAD




BTI




BTI+AC
MP



BTI+AC
MP+A
MC



BTI+A
MC



CMP-H
UT



INT



KV
KENTALROOF



SFC



SIL-C /
SIL-CN

APPLICATIONS

Designed for deck or roof mounting, they are indicated for:

- Smoke extraction.
- Air renewal in all types of buildings and industries.
- Maximum continuous working temperature: transported air 120°C, ambient 60°C to -25°C in three-phase motors.
- Special construction for moving air at 120°C

UNDER REQUEST

- Special voltages.

Technical data

Single-phase motor / 4 poles

Code	Model	R.P.M.	Rated I. A 230V	Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
27931471ALMT	KENTALROOF-A 315 M4 0,25kW 120°C	1410	1,6	0,25	2.590	-	35,50	1
27935471ALMT	KENTALROOF-A 355 M4 0,25kW 120°C	1410	1,6	0,25	3.610	-	41	1
27940480ALMT	KENTALROOF-A 400 M4 0,55kW 120°C	1400	3,98	0,55	5.340	-	45	1

Three-phase motor / 2 poles

Code	Model	R.P.M.	Rated I. A		Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
			230V	400V					
27931290ALT	KENTALROOF-A 315 T2 1,5kW 120°C	2865	5,83	3,14	1,50	5.260	-	36	2

Three-phase motor / 4 poles

Code	Model	R.P.M.	Rated I. A		Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
			230V	400V					
27931471ALT	KENTALROOF-A 315 T4 0,25kW 120°C	1400	1,38	0,79	0,25	2.590	-	35,50	2
27935471ALT	KENTALROOF-A 355 T4 0,25kW 120°C	1400	1,38	0,79	0,25	3.610	-	41	2
27940480ALT	KENTALROOF-A 400 T4 0,55kW 120°C	1440	2,57	1,49	0,55	5.340	-	45	2
27945490ALT	KENTALROOF-A 450 T4 1,1kW 120°C	1450	4,33	2,49	1,10	7.870	-	85	2
27950491ALT	KENTALROOF-A 500 T4 1,5kW 120°C	1450	5,67	3,26	1,50	10.430	-	96	2
279564100ALT	KENTALROOF-A 560 T4 3kW 120°C	1420	10,7	6,17	3,00	15.040	-	104	2
279634132ALT	KENTALROOF-A 630 T4 5,5kW 120°C	1460	-	10,5	5,50	22.550	-	140	2

Three-phase motor / 6 poles

Code	Model	R.P.M.	Rated I. A		Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
			230V	400V					
27950680ALT	KENTALROOF-A 500 T6 0,55kW 120°C	900	3,00	1,8	0,55	6.850	-	95	2
27956690ALT	KENTALROOF-A 560 T6 1,1kW 120°C	925	4,83	2,78	1,10	10.020	-	103	2
279634100ALT	KENTALROOF-A 630 T6 1,5kW 120°C	940	6,45	3,71	1,50	14.820	-	130	2


2 speed motor / 4/8 poles

Code	Model	R.P.M.	Rated I. A 400V	Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
27931471AL2VT	KENTALROOF-A 315 T4/T8 0,25/0,03kW 120°C	1370	1,13/0,37	0,25	2.590	-	35,50	3
27935471AL2VT	KENTALROOF-A 355 T4/T8 0,25/0,03kW 120°C	1370	1,13/0,37	0,25	3.610	-	41	3
27940480AL2VT	KENTALROOF-A 400 T4/T8 0,75/0,12kW 120°C	1400	2,03/0,68	0,75	5.340	-	45	3
27945490AL2VT	KENTALROOF-A 450 T4/T8 1,1/0,18kW 120°C	1400	2,67/1,08	1,10	7.870	-	85	3
27950491AL2VT	KENTALROOF-A 500 T4/T8 1,5/0,25kW 120°C	1400	3,46/1,27	1,50	10.430	-	96	3
279564100AL2VT	KENTALROOF-A 560 T4/T8 3/0,55kW 120°C	1430	6,53/2,33	3,00	15.040	-	104	3
279634132AL2VT	KENTALROOF-A 630 T4/T8 5,5/1,1kW 120°C	1450	10,73/3,82	5,50	22.550	-	140	3

Notes:

** Total sound pressure level at the point of maximum flow measured in dB(A) in the suction measured in free field at a distance of 6m from the source

Dimensions




Model	A (int)	B	C	D
KENTALROOF-A 315 M4 0,25kW 120°C	592	760	601	365
KENTALROOF-A 315 T2 1,5kW 120°C	592	760	601	365
KENTALROOF-A 315 T4 0,25kW 120°C	592	760	601	365
KENTALROOF-A 315 T4/T8 0,25/0,03kW 120°C	592	760	601	365
KENTALROOF-A 355 M4 0,25kW 120°C	662	860	624.5	365
KENTALROOF-A 355 T4 0,25kW 120°C	662	860	624.5	365
KENTALROOF-A 355 T4/T8 0,25/0,03kW 120°C	662	860	624.5	365
KENTALROOF-A 400 M4 0,55kW 120°C	662	860	647.5	365
KENTALROOF-A 400 T4 0,55kW 120°C	662	860	647.5	365
KENTALROOF-A 400 T4/T8 0,75/0,12kW 120°C	662	860	647.5	365
KENTALROOF-A 450 T4 1,1kW 120°C	936	1220	775.8	470
KENTALROOF-A 450 T4/T8 1,1/0,18kW 120°C	936	1220	775.8	470
KENTALROOF-A 500 T4 1,5kW 120°C	936	1220	812	470
KENTALROOF-A 500 T6 0,55kW 120°C	936	1220	812	470
KENTALROOF-A 500 T4/T8 1,5/0,25kW 120°C	936	1220	812	470
KENTALROOF-A 560 T4 3kW 120°C	936	1220	849.6	470
KENTALROOF-A 560 T6 1,1kW 120°C	936	1220	849.6	470
KENTALROOF-A 560 T4/T8 3/0,55kW 120°C	936	1220	849.6	470



Model	A (int)	B	C	D
KENTALROOF-A 630 T4 5,5kW 120°C	1035	1340	942.5	520
KENTALROOF-A 630 T6 1,5kW 120°C	1035	1340	942.5	520
KENTALROOF-A 630 T4/T8 5,5/1,1kW 120°C	1035	1340	942.5	520

Wiring diagram

Wiring diagram N° 1




Wiring diagram N° 2





Wiring diagram Nº 3

400V DAHLANDER (Y,YY)

LOW SPEED
VELOCIDAD BAJA




HIGH SPEED
VELOCIDAD ALTA




CHARACTERISCTIC CURVE

- | | | | | | |
|---|--------------------------------------|---|--------------------------------------|---|--------------------------------------|
| 1 | KENTALROOF-A 315 M4 0,
25kW 120°C | 2 | KENTALROOF-A 355 M4 0,
25kW 120°C | 3 | KENTALROOF-A 400 M4 0,
55kW 120°C |
|---|--------------------------------------|---|--------------------------------------|---|--------------------------------------|

AIR FLOW - PRESSURE




AIR FLOW - ABSORBED POWER




1 KENTALROOF-A 315 T2 1,
5kW 120°C

AIR FLOW - PRESSURE




AIR FLOW - ABSORBED POWER




1	KENTALROOF-A 315 T4 0, 25kW 120°C	2	KENTALROOF-A 355 T4 0, 25kW 120°C	3	KENTALROOF-A 400 T4 0, 55kW 120°C	4	KENTALROOF-A 450 T4 1, 1kW 120°C
5	KENTALROOF-A 500 T4 1, 5kW 120°C	6	KENTALROOF-A 560 T4 3kW 120°C	7	KENTALROOF-A 630 T4 5, 5kW 120°C		

AIR FLOW - PRESSURE




AIR FLOW - ABSORBED POWER




- 1 KENTALROOF-A 500 T6 0, 55kW 120°C
- 2 KENTALROOF-A 560 T6 1, 1kW 120°C
- 3 KENTALROOF-A 630 T6 1, 5kW 120°C

AIR FLOW - PRESSURE




AIR FLOW - ABSORBED POWER




1	KENTALROOF-A 315 T4/T8 0,25/0,03kW 120°C	2	KENTALROOF-A 355 T4/T8 0,25/0,03kW 120°C	3	KENTALROOF-A 400 T4/T8 0,75/0,12kW 120°C	4	KENTALROOF-A 450 T4/T8 1,1/0,18kW 120°C
5	KENTALROOF-A 500 T4/T8 1,5/0,25kW 120°C	6	KENTALROOF-A 560 T4/T8 3/0,55kW 120°C	7	KENTALROOF-A 630 T4/T8 5,5/1,1kW 120°C		

AIR FLOW - PRESSURE (4 poles)



1	KENTALROOF-A 315 T4/T8 0,25/0,03kW 120°C	2	KENTALROOF-A 355 T4/T8 0,25/0,03kW 120°C	3	KENTALROOF-A 400 T4/T8 0,75/0,12kW 120°C	4	KENTALROOF-A 450 T4/T8 1,1/0,18kW 120°C
5	KENTALROOF-A 500 T4/T8 1,5/0,25kW 120°C	6	KENTALROOF-A 560 T4/T8 3/0,55kW 120°C	7	KENTALROOF-A 630 T4/T8 5,5/1,1kW 120°C		

AIR FLOW - PRESSURE (8 poles)



Sound data

Sound / 2 poles

Sound power Lw dB (A)										
Model		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
KENTALROOF-A 315 T2 1,5kW 120°C ()	Radiated	68	72	82	79	76	79	80	65	85

Sound / 4 poles

Sound power Lw dB (A)										
Model		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
KENTALROOF-A 315 M4 0,25kW 120°C ()	Radiated	52	56	66	63	59	63	63	48	69
KENTALROOF-A 315 T4 0,25kW 120°C ()	Radiated	52	56	66	63	59	63	63	48	69
KENTALROOF-A 355 M4 0,25kW 120°C ()	Radiated	56	66	64	64	62	69	56	50	71
KENTALROOF-A 355 T4 0,25kW 120°C ()	Radiated	56	66	64	64	62	69	56	50	71
KENTALROOF-A 400 M4 0,55kW 120°C ()	Radiated	59	70	68	67	66	72	59	54	74
KENTALROOF-A 400 T4 0,55kW 120°C ()	Radiated	59	70	68	67	66	72	59	54	74
KENTALROOF-A 450 T4 1,1kW 120°C ()	Radiated	63	71	70	71	70	76	62	56	78
KENTALROOF-A 500 T4 1,5kW 120°C ()	Radiated	67	74	74	75	73	79	66	60	81
KENTALROOF-A 560 T4 3kW 120°C ()	Radiated	87	81	81	80	80	75	64	62	81
KENTALROOF-A 630 T4 5,5kW 120°C ()	Radiated	91	85	84	84	83	80	67	65	86

Sound / 6 poles

Sound power Lw dB (A)										
Model		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
KENTALROOF-A 500 T6 0,55kW 120°C ()	Radiated	58	65	64	65	64	70	57	50	72
KENTALROOF-A 560 T6 1,1kW 120°C ()	Radiated	81	75	75	74	74	70	58	56	75
KENTALROOF-A 630 T6 1,5kW 120°C ()	Radiated	82	75	75	74	74	71	58	56	76

Sound / 4/8 poles

Sound power Lw dB (A)										
Model		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
KENTALROOF-A 315 T4/T8 0,25/0,03kW 120°C (8p -)	Radiated	36	40	50	47	44	47	47	33	53
KENTALROOF-A 315 T4/T8 0,25/0,03kW 120°C (4p -)	Radiated	52	56	66	63	59	63	63	48	69
KENTALROOF-A 355 T4/T8 0,25/0,03kW 120°C (8p -)	Radiated	40	50	48	48	47	53	40	34	55
KENTALROOF-A 355 T4/T8 0,25/0,03kW 120°C (4p -)	Radiated	56	66	64	64	62	69	56	50	71
KENTALROOF-A 400 T4/T8 0,75/0,12kW 120°C (8p -)	Radiated	43	54	52	51	50	56	43	38	59
KENTALROOF-A 400 T4/T8 0,75/0,12kW 120°C (4p -)	Radiated	59	70	68	67	66	72	59	54	74
KENTALROOF-A 450 T4/T8 1,1/0,18kW 120°C (8p -)	Radiated	48	55	55	56	54	60	47	41	62
KENTALROOF-A 450 T4/T8 1,1/0,18kW 120°C (4p -)	Radiated	63	71	70	71	70	76	62	56	78
KENTALROOF-A 500 T4/T8 1,5/0,25kW 120°C (8p -)	Radiated	51	58	58	59	57	63	50	44	66
KENTALROOF-A 500 T4/T8 1,5/0,25kW 120°C (4p -)	Radiated	67	74	74	75	73	79	66	60	81
KENTALROOF-A 560 T4/T8 3/0,55kW 120°C (8p -)	Radiated	71	65	65	64	64	60	48	46	66
KENTALROOF-A 560 T4/T8 3/0,55kW 120°C (4p -)	Radiated	87	81	81	80	80	75	64	62	81
KENTALROOF-A 630 T4/T8 5,5/1,1kW 120°C (8p -)	Radiated	75	69	69	68	67	64	52	49	70
KENTALROOF-A 630 T4/T8 5,5/1,1kW 120°C (4p -)	Radiated	91	85	84	84	83	80	67	65	86