


KIT TE + HM



AXIAL WITH FIBERGLASS COWL

MANUFACTURING FEATURES:

- Roof cowl made of reinforced fibreglass.
- Roof base support and bird protection guard with polyester powder coat finishing.
- HM fans.(tubular). Supplied disassembled from del cover and base.
- Variable pitch angle Polypropylene impeller (A2 profile) or polyamide impeller reinforced with fibreglass (other profiles).
- Squirrel cage asynchronous standard motor, IP-55 protection and rated class F insulation. Standard voltages 2230V 50Hz for single phase motors, 230/400V 50Hz for three phase motors.

APPLICATIONS:

Specially designed for roof installation, they are suitable for:

- Air renewal in buildings and industries.
- Smoke extraction.
- Maximum working temperature: 1ph 50°C, 3ph 60°C.

AVAILABLE ON REQUEST

- B form impeller (air flow from impeller to motor)
- Reversible impeller 100%
- Cast aluminium impellers.
- 60Hz fans and special voltages.
- 2 speed motors.
- Hot dip galvanised and stainless steel housings.
- Galvanised steel sheet cowl.

Technical data

Single-phase motor / 4 poles

Code	Model	R.P.M.	Rated I. A 230V	Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
KTE35+26136130 635P	KIT TE + HM 35 M4 0,12kW (A0:6) 35º	1380	0,93	0,12	2.320	41	16	1
KTE40+26141230 635P	KIT TE + HM 40 M4 0,25kW (A0:6) 35º	1410	1,6	0,25	3.290	44	20	1
KTE45+26146430 640P	KIT TE + HM 45 M4 0,55kW (A0:6) 40º	1400	3,98	0,55	4.950	47	28	1

Three-phase motor / 4 poles

Code	Model	R.P.M.	Rated I. A		Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
			230V	400V					
KTE35+2613616 0635P	KIT TE + HM 35 T4 0,12kW (A0: 6) 35º	1400	0,8	0,46	0,12	2.320	41	16	2
KTE40+2614126 0635P	KIT TE + HM 40 T4 0,25kW (A0: 6) 35º	1400	1,38	0,79	0,25	3.290	44	20	2
KTE45+2614646 0640P	KIT TE + HM 45 T4 0,55kW (A0: 6) 40º	1440	2,57	1,49	0,55	4.950	47	28	2
KTE56+2615736 2633P	KIT TE + HM 56 T4 0,75kW (A2: 6) 32,5º	1410	2,83	1,63	0,75	8.440	54	36	2
KTE63+2616456 2635P	KIT TE + HM 63 T4 1,5kW (A2:6) 35º	1450	5,67	3,26	1,50	12.940	56	53	2
KTE71+2617246 2635P	KIT TE + HM 71 T4 2,2kW (A2:6) 35º	1435	8,07	4,64	2,20	18.030	59	61	2
KTE80+2618146 2635P	KIT TE + HM 80 T4 3kW (A2:6) 35º	1420	10,7	6,17	3,00	24.170	63	100	2
KTE90+2619126 6328P	KIT TE + HM 90 T4 4kW (A6:3) 28º	1440	14,5	8,32	4,00	30.230	66	115	2

Three-phase motor / 6 poles


Code	Model	R.P.M.	Rated I. A		Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
			230V	400V					
KTE63+2616546 2635P	KIT TE + HM 63 T6 0,55kW (A2: 6) 35º	900	3,00	1,8	0,55	8.390	47	53	2
KTE71+2617346 2640P	KIT TE + HM 71 T6 0,75kW (A2: 6) 40º	925	3,39	1,95	0,75	12.630	51	61	2
KTE80+2618246 2640P	KIT TE + HM 80 T6 1,1kW (A2:6) 40º	925	4,83	2,78	1,10	17.120	52	100	2

Code	Model	R.P.M.	Rated I. A		Rated power kW	Max. Airflow m³/h	Sound db (A)**	Weight kg	Connect. diagram
			230V	400V					
KTE90+2619236 6332P	KIT TE + HM 90 T6 1,5kW (A6:3) 32º	940	6,45	3,71	1,50	31.130	58	115	2
KTE100+261065 66628P	KIT TE + HM 100 T6 4kW (A6:6) 28º	1440	15,2	8,8	4,00	28.480	67	254	2

Notes:

** Total sound pressure level at the point of maximum flow measured in dB(A) in the suction measured in free field at a distance of 6m from the source

Dimensions




Model	A	B	C	D	E	F	G	H	T
KIT TE + HM 35 M4 0,12kW (A0:6) 35°	600	230	330	40	365	775	630	535	12
KIT TE + HM 35 T4 0,12kW (A0:6) 35°	600	230	330	40	365	775	630	535	12
KIT TE + HM 40 M4 0,25kW (A0:6) 35°	700	230	430	40	403	775	630	535	12
KIT TE + HM 40 T4 0,25kW (A0:6) 35°	700	230	430	40	403	775	630	535	12
KIT TE + HM 45 M4 0,55kW (A0:6) 40°	715	255	420	40	452	960	710	590	14
KIT TE + HM 45 T4 0,55kW (A0:6) 40°	715	255	420	40	452	960	710	590	14



Model	A	B	C	D	E	F	G	H	T
KIT TE + HM 56 T4 0,75kW (A2:6) 32, 5º	878	290	538	50	559	1080	905	750	14
KIT TE + HM 63 T4 1,5kW (A2:6) 35º	938	350	538	50	633	1290	905	750	14
KIT TE + HM 63 T6 0,55kW (A2:6) 35º	938	350	538	50	633	1290	905	750	14
KIT TE + HM 71 T4 2,2kW (A2:6) 35º	1010	350	610	50	715	1290	1100	840	14
KIT TE + HM 71 T6 0,75kW (A2:6) 40º	1010	350	610	50	715	1290	1100	840	14
KIT TE + HM 80 T4 3kW (A2:6) 35º	1132.5	518.5	564	50	801	1580	1100	840	14
KIT TE + HM 80 T6 1,1kW (A2:6) 40º	1132.5	518.5	564	50	801	1580	1100	840	14
KIT TE + HM 90 T4 4kW (A6:3) 28º	1390.5	518.5	822	50	903.5	1580	1250	840	14
KIT TE + HM 90 T6 1,5kW (A6:3) 32º	1390.5	518.5	822	50	903.5	1580	1250	840	14
KIT TE + HM 100 T6 4kW (A6:6) 28º	1388	518.5	820	50	903.5	1580	1250	840	14

Wiring diagram

Wiring diagram N° 1



Wiring diagram N° 2




CHARACTERISCTIC CURVE

1 KIT TE + HM 35 M4 0,
12kW (A0:6) 35º

2 KIT TE + HM 40 M4 0,
25kW (A0:6) 35º


3 KIT TE + HM 45 M4 0,
55kW (A0:6) 40º

AIR FLOW - PRESSURE



1	KIT TE + HM 35 T4 0, 12kW (A0:6) 35º	2	KIT TE + HM 40 T4 0, 25kW (A0:6) 35º	3	KIT TE + HM 45 T4 0, 55kW (A0:6) 40º	4	KIT TE + HM 56 T4 0, 75kW (A2:6) 32,5º
5	KIT TE + HM 63 T4 1,5kW (A2:6) 35º	6	KIT TE + HM 71 T4 2,2kW (A2:6) 35º	7	KIT TE + HM 80 T4 3kW (A2:6) 35º	8	KIT TE + HM 90 T4 4kW (A6:3) 28º

AIR FLOW - PRESSURE



1 KIT TE + HM 63 T6 0,
55kW (A2:6) 35°


2 KIT TE + HM 71 T6 0,
75kW (A2:6) 40°

3 KIT TE + HM 80 T6 1,1kW
(A2:6) 40°


4 KIT TE + HM 90 T6 1,5kW
(A6:3) 32°

5 KIT TE + HM 100 T6 4kW
(A6:6) 28°

AIR FLOW - PRESSURE



AIR FLOW - ABSORBED POWER



Sound data

Sound / 4 poles

Sound power Lw dB (A)										
Model		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
KIT TE + HM 35 M4 0,12kW (A0:6) 35° ()	Inlet	39	47	54	57	60	61	62	56	67
KIT TE + HM 35 T4 0,12kW (A0:6) 35° ()	Inlet	39	47	54	57	60	61	62	56	67
KIT TE + HM 40 M4 0,25kW (A0:6) 35° ()	Inlet	43	50	56	59	63	64	65	58	70
KIT TE + HM 40 T4 0,25kW (A0:6) 35° ()	Inlet	43	50	56	59	63	64	65	58	70
KIT TE + HM 45 M4 0,55kW (A0:6) 40° ()	Inlet	47	54	60	63	66	67	68	61	73
KIT TE + HM 45 T4 0,55kW (A0:6) 40° ()	Inlet	47	54	60	63	66	67	68	61	73
KIT TE + HM 56 T4 0,75kW (A2:6) 32,5° ()	Inlet	52	59	65	71	73	75	75	70	80
KIT TE + HM 63 T4 1,5kW (A2:6) 35° ()	Inlet	53	60	65	72	74	77	77	71	82
KIT TE + HM 71 T4 2,2kW (A2:6) 35° ()	Inlet	57	64	69	75	77	80	80	74	85
KIT TE + HM 80 T4 3kW (A2:6) 35° ()	Inlet	61	68	74	78	81	84	84	77	89
KIT TE + HM 90 T4 4kW (A6:3) 28° ()	Inlet	64	69	77	82	84	86	87	81	92

Sound / 6 poles

Sound power Lw dB (A)										
Model		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
KIT TE + HM 63 T6 0,55kW (A2:6) 35° ()	Inlet	43	50	56	63	65	67	68	62	73
KIT TE + HM 71 T6 0,75kW (A2:6) 40° ()	Inlet	49	56	62	67	70	71	71	65	77
KIT TE + HM 80 T6 1,1kW (A2:6) 40° ()	Inlet	52	60	65	68	72	73	72	66	78
KIT TE + HM 90 T6 1,5kW (A6:3) 32° ()	Inlet	56	62	69	76	77	78	79	73	84
KIT TE + HM 100 T6 4kW (A6:6) 28° (28°)	Inlet	63	72	78	85	86	86	87	82	93